

SERVICES

DATA CENTER

INDUSTRY



Class A chillers and heat pumps

TAL

air condensed with scroll compressors

Range: 283.2-1165.9 kW



The new TAL range chillers and heat pumps are air/water units in energy class A for both cooling and heating, available for use with R410A refrigerant or, in the “A2L” version, with low environmental impact R454B refrigerant. The TAL range is designed to manage the conditioning of industrial plants and thermal loads in technological applications, where 24/7 reliability in all working conditions, one of the assets of these units, is a critically important requirement. The TAL range uses latest generation scroll compressors, braze-welded plate exchangers optimised for use with high pressure refrigerants (R410A/R454B) and axial fans suitable for outdoor installation.

Main advantages

Easy maintenance

To carry out maintenance of the condensing coil manifolds and refrigeration circuit components, which are located behind the electrical panel, the TAL range is supplied as standard with the Hi-Rail sliding guide. This allows the control panel to be easily removed, resulting in extra space for unscheduled maintenance, without impacting the footprint required for normal operation of the unit.



Plate heat exchangers

The TAL range uses braze-welded plate exchangers with asymmetrical channels, suitable for the use of high and medium pressure refrigerant gases. The configuration with asymmetrical channels allows high exchange efficiencies to be reached while maintaining pressure drops low on the water side – reducing pumping costs at both full and partial load.

Maximised energy efficiency

The units of the TAL range fall within the energy efficiency class A, in both the chilling only version and the heat pump version. This is thanks to a careful selection of internal components, which also includes the adoption of innovative high efficiency scroll compressors with direct start, permanent magnet motor technology. The high modulation range guaranteed by the multi-scroll technology allows cooling/heating requirements to be met at any time, minimising energy waste and increasing seasonal efficiency.



Technological components



Multi-protocol communication interface

HiRef units can be integrated with the customer's external supervision Building Management System (BMS), using the most popular communication protocols, including Modbus RTU, Modbus/IP, BacNet, LonWorks, SNMP.



Scroll compressors

Scroll compressors include a mobile scroll, driven by the motor, which completes orbital revolutions and a fixed scroll that is coupled to it. The orbital motion creates a series of gas pockets that move from one scroll to the other. When moving closer to the centre of the scroll, where exhaust takes place, the gas is compressed to smaller and smaller volumes until the desired delivery pressure is reached. Scroll technology improves volumetric efficiency and flow continuity, reduces noise and leakage and eliminates harmful volumes and downtime.



Axial fans

In axial fans air moves in a parallel direction to the rotation axis and allows large air flows to be processed. Thanks to their low head compared to radial fans, they are used on remote condensers and on components with free outlet into the atmosphere, where there are no high pressure drops due, for example, to ducting.



Corrosion resistant material

The HiRef outdoor units are protected by a metal structure resistant to corrosion and weathering. They are also made of galvanised steel sheet, with epoxy-polyester powder coating, oven-polymerised at 180°C, to offer a C3 degree of protection. On request, it is possible to order specific paint finishing treatments or a metalwork structure built entirely in stainless steel, to obtain a higher degree of protection from high impact adverse weather events.



A2L Ready

Some ranges of liquid chillers, in addition to safety class A1 refrigerants R410A and R134a, can also be supplied with class A2L slightly flammable refrigerants with low environmental impact R454B and R1234ze. HiRef makes these product sub-ranges available also in the "A2L Ready" version, filled with a safety class A1 refrigerant, factory-ready and equipped with all the necessary safety sensors to allow, if the customer requests it, fast refrigerant switching at a later stage.



Low GWP refrigerant

The Global Warming Potential (GWP) index is a numerical indicator that identifies the environmental impact of a substance. It measures the extent to which a gas contributes to the greenhouse effect, in relation to carbon dioxide (CO₂), whose baseline value is equal to 1. This parameter is used to determine the amount in kilograms of CO₂ corresponding to the environmental impact of the release of a refrigerant gas into the atmosphere. The use of low GWP refrigerants, such as R513A, R454B, R1234ze, CO₂, allows the environmental impact of air conditioning systems to be significantly reduced.



Plate heat exchanger

Brazed plate heat exchangers ensure efficient heat transfer with minimised footprint, eliminate the need for thick frame plates and seals, and ensure high thermal power density. They have a long life cycle, are maintenance-free and withstand both high temperatures and extremely high pressures. This type of exchanger is used in a wide range of applications including cooling, heating, evaporation and condensation.



Class A

Internal high-tech components suitably chosen and sized allow the units to operate with outstanding levels of efficiency.

Available versions



COOLING ONLY



FREE-COOLING

REVERSIBLE HEAT
PUMP

Types of system



AIR/WATER



Additional benefits

- 3 different soundproofing setups available: Standard, Low Noise and Super Low Noise
- Electric control panel with IP55 protection rating
- Class A units in both chiller and heat pump modes
- Radial EC motor fans (optional)
- Electronic expansion valve
- Easy accessibility thanks to the optimisation of the internal space
- Programmable microprocessor control with proprietary software
- Compliance with ERP regulations

Technical table

TAL FS		294FS	324FS	374FS	404FS	454FS	496FS	556FS	596FS	636FS	676FS	748FS	808FS	868FS	900FS	1072FS
USER WATER TEMPERATURE 12/7°C 20% ETHYLENE GLYCOL, OUTSIDE AIR 35°C, 40% R.H.																
COOLING CAPACITY	kW	283.2	316.9	366.2	392.9	433.7	476.3	532.1	580.3	621.3	642.9	738.9	781.8	831.4	900.4	1064.6
TOTAL POWER INPUT	kW	87.3	102.9	115.1	126	147.4	152.7	176.6	193.6	201.1	216.6	229.7	251.8	264.5	293.2	352.7
EER	-	3.24	3.08	3.18	3.12	2.94	3.12	3.01	3	3.09	2.97	3.22	3.11	3.14	3.07	3.02
TAL CS		294CS	324CS	374CS	404CS	454CS	496CS	556CS	596CS	636CS	676CS	748CS	808CS	868CS	900CS	1072CS
USER WATER VALUES 12/7°C, 35°C OUTSIDE AIR, 40% U.R.																
COOLING CAPACITY	kW	286.1	319.8	370.1	397.8	450	482.7	539.7	588.7	629.9	662.1	746.6	791.3	841.2	911.8	1079.7
TOTAL POWER INPUT	kW	86.2	101.9	114	124.4	145.3	150.3	173.7	190.5	198	213.2	226.8	248.1	261.1	289.2	347.2
EER	-	3.32	3.14	3.25	3.2	3.1	3.21	3.11	3.09	3.18	3.1	3.29	3.19	3.22	3.15	3.11
SEPR	-	5.67	5.65	5.61	5.62	5.6	5.68	5.69	5.78	5.7	5.61	5.75	5.7	5.62	5.76	5.72
SEER	-	5.18	4.96	5.08	5.05	4.96	5.25	5.22	5.32	5.3	5.18	5.08	5.01	4.97	4.98	5.12
TAL FS		294FS	324FS	374FS	404FS	454FS	496FS	556FS	596FS	636FS	676FS	748FS	808FS	868FS	900FS	1072FS
UTILITY WATER TEMPERATURE 12/7°C, ETHYLENE GLYCOL 20%																
FULL FREE-COOLING TEMPERATURE	°C	-8.9	-8.4	-4.6	-5.4	-7	-4.4	-6.1	-7.6	-5.3	-5.8	-5.3	-6.2	-4.6	-6.1	-6.1
TAL HS		294HS	324HS	374HS	404HS	454HS	496HS	556HS	596HS	636HS	676HS	748HS	808HS	868HS	900HS	1072HS
USER WATER VALUES 40/45°C, 7°C OUTSIDE AIR, 89% U.R.																
THERMAL POWER	kW	292.2	334.3	395.6	421.7	474.9	513.9	573.4	625.2	674.4	706.6	769.6	829.5	884.4	960.3	1165.9
TOTAL POWER INPUT	kW	90.6	104.1	119.6	128.2	146.5	159.8	178.5	194.5	209.5	219.5	236.4	256.3	274.5	298.2	362.4
COP	-	3.22	3.21	3.31	3.29	3.24	3.22	3.21	3.21	3.22	3.22	3.26	3.24	3.22	3.22	3.22
SCOP	-	4.16	4.27	4.12	4.13	4.21	3.98	4.11								
SEER	-								5.31	5.19	5.25	4.99	4.94	4.84	4.98	5.16
SOUND POWER LEVEL	dB	89		90		92	91	92	91		93			94		95
SOUND POWER LEVEL LOW NOISE	dB	86		87		89	87	89	88		90			91		92
SOUND POWER LEVEL SUPER LOW NOISE	dB	83		85		86	85	87	86	87	88		87	88	89	90
DIMENSIONS [LxHxD]	mm	3865 x2652 x2256		4865 x2652 x2256		5860x2652x2256		6860 x2652 x2256		7865 x2652 x2256		8865 x2652 x2256		11270 x2652 x2256		

20% Ethylene glycol | Also available with 60 Hz power supply | Data declared with use of R410A refrigerant



HiRef S.p.A. reserves the right, at any time, to introduce any necessary changes and improvements to its products without prior notice. Reproduction, even partial, of this catalogue is forbidden without a written permission **HiRef S.p.A. © Copyright HiRef S.p.A. 2001-2022**