

Modular efficiency, maximum power

40 – 200 kW Range



FanWall air conditioners

chilled water or direct expansion versions
for high density hyperscale data centres



Cooling capacity meets compact footprint

Our chilled water FanWall HBCV series air conditioners are designed for technological environments where a compact footprint is a requirement – without any impact on these units' cooling output capacity. An in-depth CFD (computational fluid dynamics) analysis has allowed every last constructive detail to be designed so as to minimise internal airflow pressure drops and, therefore, fan power consumption. At the same time, the large surface of the finned pack exchanger minimises the approach temperatures between inlet air and outlet water, maximising system efficiency.



Finned pack coil with hydrophilic coating ①

All models in the FanWall HBCV range feature heat exchange coils with hydrophilic coating. This special coating – together with adequate adjustment of air through-flow speeds – helps condensate collection and outflow during the dehumidification process, preventing any dripping on the inside and outside of the unit.

Blown finned coil ③

According to a specific design choice, this finned coil is installed downstream of the fans. This ensures a more even distribution of the delivery air to the racks, minimising turbulence in the air flow.

Accurate regulation with multiple types of valves ②

The adjustment valve with 0-10V servomotor (standard on the whole range) can be obtained in a 2-way (requires variable flow system) or 3-way version. The other versions available with configurator are those with spring return servomotor or independent pressure valves. The flow control performance of this type of valve guarantees adjustment accuracy, while at the same time maintaining the hydronic balance in the system.



Ventilation EC 2.0

The use of standard-equipment EC plug fans across the whole range – designed to adjust the air flow according to the thermal load – results in efficient use of the electricity for ventilation purposes, with a positive impact on the system PUE. Extended range speed adjustment is carried out via MODBUS protocol. The emergency speed function allows for fan operation consistency even in the event of microprocessor malfunctions.

Ventilation adjustment ③

Depending on the air distribution logic in the server room, it is possible to adjust the machine on-board ventilation system to ensure a constant air flow rate (airflow control) or a constant available overpressure (p control). The latter is particularly useful if a floating floor is used.

Maximum possible redundancy

To ensure system operation continuity, the FanWall HBCV range makes it possible to have a fully redundant refrigeration circuit: a double coil and double water adjustment valve allow the server room to be cooled even when either circuit fails.

Easier scheduled maintenance ④

The unit has been designed with the utmost care to grant front (air inlet side) access to internal components even with the units running. This makes routine maintenance easier in full compliance with safety standards.



More advantages

- Double power supply with automatic switch (on request)
- Stainless steel condensate drain pan
- Fan speed modulation based on thermal load (constant ΔT)
- Fan speed modulation based on air flow requirements (constant Δp)
- Humidify/de-humidify feature
- Post-heating systems:
 - with electrical heating elements
 - with hot water coil
- instantaneous reading of the supplied cooling capacity (on request)

FANWALL HBCV		051	121	171	102	242	342
		1 MODULE			2 MODULES		
VERSION B - INLET AIR 30 °C - 35% R.H.; WATER TEMPERATURE 10 - 18 °C							
TOTAL COOLING CAPACITY	KW	48.5	118.2	173.4	97	236.4	346.8
SHR	-	1.0	1.0	1.0	1.0	1.0	1.0
REFRIGERATION CYCLE EER	-	69.3	62.2	59.8	69.3	62.2	59.8
VERSION B - INLET AIR 35 °C - 25% R.H.; WATER TEMPERATURE 10 - 18 °C							
TOTAL COOLING CAPACITY	KW	63.7	157.1	230.3	127.4	314.2	460.6
SHR	-	1.0	1.0	1.0	1.0	1.0	1.0
REFRIGERATION CYCLE EER	-	91.0	82.7	79.4	91.0	82.7	79.4
VERSION C - INLET AIR 30 °C - 35% R.H.; WATER TEMPERATURE 10 - 22 °C							
TOTAL COOLING CAPACITY	KW	44.9	110.2	164.4	89.8	220.4	328.8
SHR	-	1.0	1.0	1.0	1.0	1.0	1.0
REFRIGERATION CYCLE EER	-	64.1	58.0	56.7	64.1	58.0	56.7
VERSION C - INLET AIR 35 °C - 25% R.H.; WATER TEMPERATURE 10 - 22 °C							
TOTAL COOLING CAPACITY	KW	60.6	148.9	219.8	121.2	297.8	439.6
SHR	-	1.0	1.0	1.0	1.0	1.0	1.0
REFRIGERATION CYCLE EER	-	86.6	78.4	75.8	86.6	78.4	75.8
AIR FLOW RATE	M3/H	8700	21200	31100	17400	42400	62200
TOTAL ABSORBED POWER	KW	0.7	19	29	1.4	3.8	5.8
DIMENSIONS* (WxHxD)	MM	1500x1475x1300	2950x1475x1300	4000x1475x1300	1500x2950x1300	2950x2950x1300	4000x2950x1300

* The dimensions shown refer to standard models but can be customised according to application requirements



HiRef S.p.A reserves the right, at any time, to introduce any necessary changes and improvements in its products without prior notice. Reproduction, even partial, of this catalogue is forbidden without a written permission from HiRef S.p.A. © Copyright HiRef S.p.A. 2021-2022