

9PX G2 8000VA 8000W 208V Online Double-Conversion UPS - Hardwired Input, 4 L6-30R/Hardwired Output, Maintenance Bypass, Cybersecure Network Card, Extended Run, 4U Rack/Tower

NÚMERO DE MODELO: 9PX8KMG2



Provides sine wave output, complete battery backup and power protection for mission-critical IT installations, edge networks and other advanced network applications.

Características

8kVA/8kW/208V Battery Backup for Distributed IT and Edge Networks

This 9PX G2 rack-mount online double-conversion UPS system provides reliable, low-maintenance battery backup and AC power protection against blackouts, brownouts, surges and line noise that can damage critical IT equipment or destroy data. The 9PX8KMG2 is ideal power management for IT managers, data center managers, electrical contractors, integrators, specifying engineers and other end users in business, edge computing, education, government, healthcare, retail and other networking applications.

Delivers Maximum Power Reliability with Best-in-Class Efficiency

With unity power factor (8000VA/8000W output), the 9PX8KMG2 maximizes usable output power and allows you to support more devices, including servers, PoE switches and other networking equipment. The most efficient UPS system in its class, the 9PX8KMG2 complies with the latest ENERGY STAR standards to reduce greenhouse gas emissions and to save you money on energy and cooling costs. Load segments with energy metering help you optimize energy use.

Reliable, Expandable Battery Backup with Enhanced Management

Exclusive ABM+ technology improves predictive battery replacement analytics to better pinpoint when you should replace UPS batteries. By adding this predictive algorithm, you can determine the expected battery failure date based on real-life usage and conditions. This prevents unexpected downtime caused by waiting too long and unnecessary expense caused by replacing too soon. ABM+ also optimizes charging to increase battery lifespan up to 50%. You can connect up to 12 extended battery modules (9PXEBM240RTG2, sold separately) to add necessary runtime during prolonged power outages.

Included Maintenance Bypass For Critical Equipment

The included MBP11K208G2 maintenance bypass lets you service or replace the UPS power module without powering down any connected equipment.

Included Gigabit Network Interface Offers 24/7 Remote Access and Cybersecurity

The NETWORK-M3 cybersecure network management card enables full remote configuration and

Destacado

- Keeps equipment running during outages to allow time for file saves and safe shutdown
- Best-in-class efficiency results in reduced energy costs and greenhouse gas emissions
- Included NETWORK-M3 Gigabit network card enables full remote access and control
- Exclusive ABM+ technology and analytics help you pinpoint when to replace batteries
- Optional extended battery modules allow expanded runtime to keep equipment powered

El Paquete Incluye

- 8000VA 8000W 208V 9PX G2 Online Double-Conversion UPS
- MBP11K208G2 Maintenance bypass
- NETWORK-M3 Gigabit network card
- USB cable
- RS-232 cable
- Cable gland for hardwire connection
- Rack-mounting hardware
- Tower stands
- Quick Start Guide

PARA MÁS INFORMACIÓN o PREGUNTAS CONSULTA A TU ASESOR, ESTAMOS PARA AYUDARTE



Síguenos en las redes sociales para obtener la información más reciente de productos y servicios





management, including load shedding, reboots of connected equipment and safe shutdowns. UPS firmware can also be flashed remotely through the NETWORK-M3 without dropping the load, so you don't have to plan for downtime. The card meets both UL 2900-1 and IEC 62443-4-2 standards for cybersecurity, which were developed to address the vulnerability of connected devices to known malware/exploits and to protect business from these risks.

High-Visibility LCD Interface Keeps You Informed at a Glance


The high-contrast color LCD provides control settings and critical information to help diagnose any issues. A large color LED bar makes it easy to diagnose UPS status from a distance and quickly locate units that require attention. The interface rotates to accommodate both rack-mount and tower configurations, and it tilts up to 45 degrees for more comfortable viewing.

Ready for Virtualization, HCI and Generative AI

Brightlayer software provides simple yet powerful fleet management. You can remotely manage UPS systems in diverse IT environments across multiple distributed sites from one location, maintain uptime and improve operational efficiency. Brightlayer also enables intelligent coordination with virtualized, hyperconverged and generative AI infrastructure, including complex orchestrations during blackouts and other power events to extend runtime and preserve data.

Versatile Installation Options

You can mount the 9PX8KMG2 in just 4U of space in an EIA-standard 19-inch rack using the included 4-post rail kit or use the optional RK2PC rail kit (sold separately) for mounting in a 2-post rack. You can also adapt it for tower installation with the included stands. A cable gland is included for hardwire input.

**PARA MÁS INFORMACIÓN o PREGUNTAS
CONSULTA A TU ASESOR,
ESTAMOS PARA AYUDARTE** 

Síguenos en las redes sociales para obtener la información más reciente de productos y servicios



Especificaciones

| GENERALIDADES | |
|--|---|
| Código UPC | 037332295439 |
| Tipo de UPS | En Línea |
| ENTRADA | |
| Fase de Entrada | Monofásico |
| Corriente especificada de entrada (Carga Máxima) | 38.4A |
| Voltaje(s) Nominal(es) de Entrada Soportado(s) | 200V CA; 208V CA; 220V CA; 230V CA; 240V CA |
| Tipo de conexión de entrada del UPS | Instalación Eléctrica Permanente |
| Tipo de Clavija de Alimentación | Hard-wire |
| SALIDA | |
| Capacidad de Salida (VA) | 8000 |
| Capacidad de Salida (kVA) | 8 |
| Capacidad de Salida (Watts) | 8000 |
| Capacidad de Salida (kW) | 8 |
| Factor de Potencia | 1 |
| Factor de Cresta | 3:1 |
| Detalles del Voltaje Nominal | 200V, 208V, 220V, 230V, 240V |

| | |
|---|--|
| Compatibilidad de Frecuencia | 50Hz / 60Hz |
| Forma de onda de CA de salida (Modo en Batería) | Onda Sinusoidal Pura |
| Voltaje(s) Nominal(es) de Salida Soportado(s) | 200V; 208V; 220V; 230V; 240V |
| Tomacorrientes | Instalación Eléctrica Permanente; (4) L6-30R |
| Bancos de Carga Controlables Individualmente | Sí |
| BATERÍA | |
| Tipo de Batería | Plomo Ácido Regulada por Válvula [VRLA] |
| Autonomía a Plena Carga (min) | 5.4 min. (8000W) |
| Autonomía a Media Carga (min) | 15.2 min. (4000W) |
| Autonomía Ampliable | Sí |
| Descripción del tiempo de autonomía ampliable | Add up to 12 extended battery modules (EBM). Part number 9PXEBM240RTG2 |
| Voltaje CD del sistema (VCD) | 240 |
| Tasa de Recarga de Baterías (Baterías Incluidas) | Batteries recharge to 90% capacity in less than 3 hours |
| Acceso a la Batería | Battery access door |
| Cartucho de Baterías Internas de Reemplazo para UPS | EBP-2003 |
| Descripción de reemplazo de batería | Hot-swappable, user replaceable batteries. UPS requires 2 Replacement Battery Cartridges. |
| Administración de la Batería | ABM+ technology (predictive battery replacement analytics to pinpoint when you should replace UPS batteries. 3-stage charging extends battery service life by 50%.) |
| INTERFAZ DE USUARIO, ALERTAS Y CONTROLES | |
| Pantalla LCD del Panel Frontal | LCD graphical display |
| Interruptores | RPO / ROO |
| Operación para Cancelar la Alarma | Press ESC to silence the alarm |
| Alarma Acústica | Audible alarm indicates utility failure, low-battery, overload, other UPS/Battery fault or remote shutdown conditions |
| Indicadores LED | LED status bar |
| SUPRESIÓN DE SOBRECARGA / RUIDO | |
| Tiempo de respuesta de supresión de CA del UPS | 0 ms |
| Supresión de Ruido EMI / RFI en CA | Sí |
| Tiempo de respuesta de supresión de CA | 0 ms |
| FÍSICAS | |
| Factor de Forma Primario | Para instalación en rack; Torre |

| | |
|---|--|
| Altura del Rack | 4U |
| Método de Enfriamiento | Fan |
| Los Factores de Forma de Instalación Son Soportados con los Accesorios Opcionales | Instalación en rack de 4 postes de 19; Torre |
| Los Factores de Forma de Instalación Son Soportados con los Accesorios Opcionales | 2 post rackmount (2 post rackmount) |
| Profundidad Mínima de Rack Requerida (cm) | 83.82 |
| Profundidad Mínima de Rack Requerida (Pulgadas) | 33 |
| Peso del Módulo de Potencia del UPS (kg) | 78.79 |
| Peso del Módulo de potencia del UPS (lb) | 173.7 |
| Dimensiones de la Unidad (Al x An x Pr / pulgadas) | 6.800 x 17.300 x 32.600 |
| Peso de la Unidad (lb) | 188.7 |
| Peso de la Unidad (kg) | 85.59 |
| AMBIENTALES | |
| Rango de Temperatura de Operación | 32° to 104°F (0° to 40°C) |
| Humedad Relativa | 0-95% non-condensing |
| Clasificación de eficiencia del modo de CA (100% de carga) | 96.5 |
| Clasificación de eficiencia del modo económico de CA (100% de carga) | 99.4 |
| Disipación de calor en modo en línea (BTU/Hr) a carga completa | 815 |
| Disipación térmica en modo batería (BTU/Hr) a carga completa | 1137 |
| COMUNICACIONES | |
| Tarjetas de Administración de Red | INDGW-M2 ; RELAY-MS ; Network-M3 |
| Interfaz de Comunicaciones | Tarjeta de red preinstalada; RS-232; USB |
| CARACTERISTICAS/ESPECIFICACIONES | |
| Funciones del UPS de alta disponibilidad | Expandable battery backup; Baterías Hot-Swap; On-Line/Double-Conversion; Pure sine wave output; Remote management; Surge/noise protection |
| APLICACIONES | |
| Aplicaciones de UPS | Mission Critical Applications |



Powering Business Worldwide



TRIPP-LITE
by Eaton

| ESTÁNDARES Y COMPATIBILIDAD | |
|---|--|
| Certificaciones del Producto | NOM (Mexico); cUL Listed; EN 62040-2 |
| Product Compliance | FCC Parte 15 Clase A (EE UU); CE (Europa); FCC (EE UU); Calificación ENERGY STAR; RoHS |
| GARANTÍA y SOPORTE | |
| Periodo de garantía del producto (USA y Canadá) | Garantía limitada de 3 años. |
| Planes de Servicio Extendido | ADVANCED DEPOT EXCHANGE Service Part Number: 9SW5Y-11000UC Expedited parts coverage for 5 years Parts, electronics and UPS batteries coverage Next business day shipping Technical support 5-YEAR ON-SITE PLAN (US ONLY) Service Part Number: WFLN75XX-11000UC On-site parts and labor coverage for years 5 Parts, electronics and UPS batteries coverage 24x7 on-site labor coverage, next-day response Next-day shipping Technical support |

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.

PARA MÁS INFORMACIÓN o PREGUNTAS
CONSULTA A TU ASESOR,
ESTAMOS PARA AYUDARTE 

Síguenos en las redes sociales para obtener la
información más reciente de productos y servicios

